



STANDARD CAPACITY :

10 , 15 , 20 , 25 , 30 , 40 , 50t

WIRING:

RED +INPUT GREEN +OUTPUT
 BLACK -INPUT WHITE -OUTPUT
 4 COLOR SHIELD CABLE 20FT(6m)

● Specifications

Rated output	2.0mV/V±0.1%
Accuracy class	0.03
Non-linearity	0.03% F·S
Hysteretic	0.03% F·S
Non-repeatability	0.02% F·S
Creep in 30 minutes	0.03% F·S
Temperature effect span	15 PPM /°C of Applied Load
Temperature effect zero	26 PPM /°C of Applied Load
Compensated temperature range	—10°C~40°C
Operating temperature range	—40°C~65°C
Zero balance	±1% F·S
Input resistance	770±40 Ω
Output resistance	700± 5 Ω
Safe overload	150%F·S
Ultimate overload	300%F·S
Excitation voltage	10VAC/DC
Maximum excitation voltage	30VAC/DC
Insulation resistance	≥ 5000M Ω (50V DC)
Environmental protection	IP67
Material	Alloy tool steel

※All specifications are a maximum as a%(±) of full load, otherwise stated.

Capacity	L1	L3	L4	L5	H	B	D
10t	240	80	100	126	199.9	136	φ 18
15,20,25,30t	240	80	100	126	229.3	136	φ 18
40,50t	340	124	124	160	261	160	φ 22

